

OPERATING TABLE RAPIDO FOR DAY SURGERY

All-in-one table for day surgery

Rapido is an all-in-one hydraulic day surgery table for preinduction, transport, operation and recovery. Its variety of features makes it the ideal solution for busy day surgery needs. Rapido enables expedient operating room transfers in the day surgery ward which leads to more efficient use of operating room time crucial in efficient outpatient surgery.

Operating table Rapido Upper Body

Rapido Upper Body operating table is specially designed for various types of surgeries on the upper body, including head. In this model there is a lot of space that enable the surgeon to come close to the patient.





Rapido features:

- Dedicated Day-Surgery table
- Cost effective: 1 product, several applications: bed, trolley, operating table, examination table
- Easy to service
- Easy to clean and to operate
- Exceptionally low minimum height
- Base frame of epoxy coated steel
- Casings of chock-resistant ABS-plastics
- Swiveling antistatic twin-castors 150

- Central locking pedal on each castor (locks all castors simultaneously)
- Robust and stable column system
- Table top of 4–5 sections (Head section included)
- Top plates are X-ray translucent high pressure laminate
- X-ray cassette rails along the full length
- Soft antistatic, 80 mm separate mattress set fixed to the table with velcro fitting
- Swing-down side rails

RAPIDO Upper Body features:

- Specialized application for various surgical procedures on the upper body
- Easy access to the upper body area
- Exceptionally low minimum height

Title	Basic	Upper Body
Features		
Applications		
Length	2050 mm	2185 mm
Width (table top)	654 mm	654 mm
Width (base)	630 mm	630 mm
Height adjustment	650 - 1020 mm	650 - 1020 mm
Safe working load (SWL)	160 kg	160 kg
Trendelenburg	-25 °	-25 °
Reverse Trendelenburg	+18 °	+18 °
Head rest adjustment	-45 - +25 °	-45 - +25 °
Back section adjustment	-4 - +70 °	-4 - +70 °
Leg section adjustment	-90 - +4 °	-90 - +4 °
Castors size	150	150
Castor type (antistatic, locking)	antistatic	antistatic
Mattress base (sections, pcs)	5	5
Mattress base (width)	600 mm	600 mm
Weight	125 kg	125 kg
Lateral tilt	-15 - +15 °	0 - 0 °
Max. lifting capacity	250 kg	250 kg
Product Code	100001860, 100001865	100001860, 100001865

